

# CLOUDBOARD

Accessories for interactive CloudBoard systems

## Active loudspeaker system Cloudspeaker

Image shows:  
CLSP with holder  
SM-HDL on CloudBoard



At the CloudBoard



With holder SM-HDL



With holder SM-HDT



### TECHNICAL DATA

Output (AES)	2 x 30 W
Frequency	55 Hz – 20 kHz
Inputs	Cinch
Input impedance	5 Ohm
Distortion	< 1 %
Signal-to-noise ratio	> -10 dB
SPL 1 W/ 1 m	88 dB
Tone control	Bass: + -12 dB bei 80 Hz, Heights: + -12 dB bei 12 kHz
Power supply	230 V
Dimensions (W/H/D)	18,3 x 24,8 x 16,4 cm
Weight	6,05 kg incl. holder, cable

### Active loudspeaker system Cloudspeaker

- White case
- Integrated amplifier, on-/off switch on the back
- Scope of delivery: Holder/bracket, cable (1,5 m), loudspeaker cable

Item no.

#### Holder

for horizontal assembly above table or CloudBoard systems

Item no.

#### Holder

for vertical assembly above table systems

Item no.

## Accessories

FIND MORE  
AUDIO SYSTEMS

170  
from page



Stroke  
50 cm

Image shows: CloudBoard EHICL161FO with Hitachi projector and fingertouch-module, see page 119



Lockable mini PC bracket  
Contact us for the available models.  
Can be mounted on left or right  
side behind the central surface.

Item no.

Active loudspeaker system  
2 x 15 W

Item no.

#### Holder

for vertical assembly above board systems

Item no.

Additional information around  
loudspeaker system: page 173.

Please add the reference of the  
required finish!

E.g. side shelf made of acrylic  
glass = LAP4-AC

If no reference is made a shelf  
in black will be supplied.

1 side shelf

- Dimensions, W/D: 45 x 32,5 cm
- Mounting at left or right side

Item no.

### Finishes


#### Solid grade laminate



..VS Black

..VG Grey

#### Acrylic glass



..AC

Satined on one side