

AUDIO

Active loudspeaker systems for conference- and class rooms

Active loudspeaker system Cloudspeaker



Image shows:
CLSP with holder
SM-HDL on Cloudboard



With holder SM-HDL



With holder SM-HDT



Active loudspeaker system Cloudspeaker

- White case
- Integrated amplifier, on-/off switch on the back
- Scope of delivery: Holder/bracket, cable (1,5 m), loudspeaker cable

Item no. CLSP

Holder

for horizontal assembly above table or Cloudboard systems

Item no. SM-HDL

Holder

for vertical assembly above table systems

Item no. SM-HDT

TECHNICAL DATA

Output (AES)	2 x 30 W
Frequency	55 Hz – 20 kHz
Inputs	Cinch
Input impedance	5 Ohm
Distortion	< 1 %
Signal-to-noise ratio	> -10 dB
SPL 1 W/ 1 m	88 dB
Tone control	Bass: + -12 dB bei 80 Hz, Heights: + -12 dB bei 12 kHz
Power supply	230 V
Dimensions (W/H/D)	18,3 x 24,8 x 16,4 cm
Weight	6,05 kg incl. holder, cable

Active loudspeaker system Cleveraudio



Image shows:
CL-AU with holder
SM-CLOUD at the board system



CL-AU



CL-AUR



Image shows:
CL-AU with
holder
SM-CLOUD at
Cloudboard

At the Cloudboard

TECHNICAL DATA

Output (AES)	2 x 15 W
Frequency	80 Hz – 20 kHz
Inputs	2 x Cinch for PC and DVD
Input impedance	6 Ohm
Distortion	< 0,3 %
Signal-to-noise ratio	> 35 dB
SPL 1 W/ 1 m	> 60 dB
Tone control	On the active loudspeaker, OPTIONAL: Cable remote control (CL-AUR)
Power supply	230 V
Dimensions (W/H/D)	14,2 x 25,0 x 13,0 cm
Weight	4,42 kg incl. holder, cable

Active loudspeaker system Cleveraudio

- White high gloss wooden case
- Integrated amplifier, on-/off switch on the back, volume control at the active loudspeaker
- Scope of delivery/ accessories: incl. wall mounting brackets, loudspeaker cable (10 m), audio in cable (cinch to 3,5 mm minijack), audio in cable (cinch to cinch), power cable

Item no. CL-AU

Cable remote control

with on/off function and volume control

Item no. CL-AUR

Holder

for horizontal assembly above table or Cloudboard systems

Item no. SM-CLOUD